


Type of luminaire	pendant / overhead
Application areas	general / accent lighting
Mounting	3P Power Track or screws to the ceiling
Pan/tilt range	--
Supply unit	LED Driver integrated (LED Driver DALI on request)
Nominal voltage	220V, 50Hz
System performance	34 W, 48 W, 68 W
Lighting technology	LED SMD 2835
Optic	PMMA
Beam angle	90°
Luminous Flux	4685 - 8663 lm
Light colour	2700 K, 3000 K, 4000 K, 5000 K
CRI	80 - 90
Power factor	0,95
Protection rating	IP20
Cooling	passive
Body	Cast aluminum
Body colour	black, white, Special colours on request
Dimensions	1410 x 54 x 61 mm
Weight	2,6 kg
Life time	50 000 hours.
Warranty	5 years/50 000 hours
Certificates	UA, CE



Beam angle options



Komo90 LED

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information – L85 / B10 at 35 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

Ordering information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
90 LED 34W/827 W	90°	34 W	80	2700 K	3326 lm
90 LED 34W/827 W					
90 LED 34W/830 W	90°	34 W	80	3000 K	3982 lm
90 LED 34W/830 B					
90 LED 34W/840 W	90°	34 W	80	4000 K	4685 lm
90 LED 34W/840 B					
90 LED 34W/850 W	90°	34 W	80	5000 K	4685 lm
90 LED 34W/850 B					
90 LED 48W/827 W	90°	48 W	80	2700 K	4522 lm
90 LED 48W/827 W					
90 LED 48W/830 W	90°	48 W	80	3000 K	5414 lm
90 LED 48W/830 B					
90 LED 48W/840 W	90°	48 W	80	4000 K	6370 lm
90 LED 48W/840 B					
90 LED 48W/850 W	90°	48 W	80	5000 K	6370 lm
90 LED 48W/850 B					
90 LED 68W/827 W	90°	68 W	80	2700 K	6151 lm
90 LED 68W/827 W					
90 LED 68W/830 W	90°	68 W	80	3000 K	7364 lm
90 LED 68W/830 B					
90 LED 68W/840 W	90°	68 W	80	4000 K	8663 lm
90 LED 68W/840 B					
90 LED 68W/850 W	90°	68 W	80	5000 K	8663 lm
90 LED 68W/850 B					
90 LED 34W/927 W	90°	34 W	90	2700 K	2905 lm
90 LED 34W/927 W					
90 LED 34W/930 W	90°	34 W	90	3000 K	3514 lm
90 LED 34W/930 B					
90 LED 34W/940 W	90°	34 W	90	4000 K	4100 lm
90 LED 34W/940 B					
90 LED 34W/950 W	90°	34 W	90	5000 K	4100 lm
90 LED 34W/950 B					
90 LED 48W/927 W	90°	48 W	90	2700 K	3949 lm
90 LED 48W/927 W					
90 LED 48W/930 W	90°	48 W	90	3000 K	4777 lm
90 LED 48W/930 B					
90 LED 48W/940 W	90°	48 W	90	4000 K	5573 lm
90 LED 48W/940 B					
90 LED 48W/950 W	90°	48 W	90	5000 K	5573 lm
90 LED 48W/950 B					
90 LED 68W/927 W	90°	68 W	90	2700 K	5371 lm
90 LED 68W/927 W					
90 LED 68W/930 W	90°	68 W	90	3000 K	6497 lm
90 LED 68W/930 B					
90 LED 68W/940 W	90°	68 W	90	4000 K	7580 lm
90 LED 68W/940 B					
90 LED 68W/950 W	90°	68 W	90	5000 K	7580 lm
90 LED 68W/950 B					

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information – L85 / B10 at 35 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra> 80 /> 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.