

Track light

Komo Track


AVA TECH

Type of luminaire	track light
Application areas	accent lighting
Mounting	3P Power Track
Pan/tilt range	355°/90°
Supply unit	LED Driver integrated (LED Driver DALI on request)
Nominal voltage	220V, 50Hz
System performance	20 W, 32 W, 45 W
Lighting technology	LED SMD 2835
Optic	PMMA
Beam angle	30°, 60°, 90°, 110°, DoubleSym, Asym
Luminous Flux	2600 - 5850 lm
Light colour	2700 K, 3000 K, 4000 K, 5000 K
CRI	80 - 90
Power factor	0,95
Protection rating	IP20
Cooling	passive
Body	Cast aluminum
Body colour	black, white, Special colours on request
Dimensions	600 x 54 x 61 mm
Weight	0,95 kg
Life time	50 000 hours
Warranty	5 years/50 000 hours
Certificates	UA, CE




Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.


Beam angle options




Komo Track 30 LED




Komo Track 60 LED




Komo Track 90 LED



Komo Track 110 LED



Komo Track DS LED



Komo Track AS LED

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

Ordering information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
30 LED 20W/827 W 30 LED 20W/827 B	30°	20 W	80	2700 K	1846 lm
30 LED 20W/830 W 30 LED 20W/830 B	30°	20 W	80	3000 K	2210 lm
30 LED 20W/840 W 30 LED 20W/840 B	30°	20 W	80	4000 K	2600 lm
30 LED 20W/850 W 30 LED 20W/850 B	30°	20 W	80	5000 K	2600 lm
30 LED 32W/827 W 30 LED 32W/827 B	30°	32 W	80	2700 K	2954 lm
30 LED 32W/830 W 30 LED 32W/830 B	30°	32 W	80	3000 K	3536 lm
30 LED 32W/840 W 30 LED 32W/840 B	30°	32 W	80	4000 K	4160 lm
30 LED 32W/850 W 30 LED 32W/850 B	30°	32 W	80	5000 K	4160 lm
30 LED 45W/827 W 30 LED 45W/827 B	30°	45 W	80	2700 K	4154 lm
30 LED 45W/830 W 30 LED 45W/830 B	30°	45 W	80	3000 K	4973 lm
30 LED 45W/840 W 30 LED 45W/840 B	30°	45 W	80	4000 K	5850 lm
30 LED 45W/850 W 30 LED 45W/850 B	30°	45 W	80	5000 K	5850 lm
60 LED 20W/827 W 60 LED 20W/827 B	60°	20 W	80	2700 K	1846 lm
60 LED 20W/830 W 60 LED 20W/830 B	60°	20 W	80	3000 K	2210 lm
60 LED 20W/840 W 60 LED 20W/840 B	60°	20 W	80	4000 K	2600 lm
60 LED 20W/850 W 60 LED 20W/850 B	60°	20 W	80	5000 K	2600 lm
60 LED 32W/827 W 60 LED 32W/827 B	60°	32 W	80	2700 K	2954 lm
60 LED 32W/830 W 60 LED 32W/830 B	60°	32 W	80	3000 K	3536 lm
60 LED 32W/840 W 60 LED 32W/840 B	60°	32 W	80	4000 K	4160 lm
60 LED 32W/850 W 60 LED 32W/850 B	60°	32 W	80	5000 K	4160 lm
60 LED 45W/827 W 60 LED 45W/827 B	60°	45 W	80	2700 K	4154 lm
60 LED 45W/830 W 60 LED 45W/830 B	60°	45 W	80	3000 K	4973 lm
60 LED 45W/840 W 60 LED 45W/840 B	60°	45 W	80	4000 K	5850 lm
60 LED 45W/850 W 60 LED 45W/850 B	60°	45 W	80	5000 K	5850 lm
90 LED 20W/827 W 90 LED 20W/827 B	90°	20 W	80	2700 K	1846 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

Ordering information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
90 LED 20W/830 W 90 LED 20W/830 B	90°	20 W	80	3000 K	2210 lm
90 LED 20W/840 W 90 LED 20W/840 B	90°	20 W	80	4000 K	2600 lm
90 LED 20W/850 W 90 LED 20W/850 B	90°	20 W	80	5000 K	2600 lm
90 LED 32W/827 W 90 LED 32W/827 B	90°	32 W	80	2700 K	2954 lm
90 LED 32W/830 W 90 LED 32W/830 B	90°	32 W	80	3000 K	3536 lm
90 LED 32W/840 W 90 LED 32W/840 B	90°	32 W	80	4000 K	4160 lm
90 LED 32W/850 W 90 LED 32W/850 B	90°	32 W	80	5000 K	4160 lm
90 LED 45W/827 W 90 LED 45W/827 B	90°	45 W	80	2700 K	4154 lm
90 LED 45W/830 W 90 LED 45W/830 B	90°	45 W	80	3000 K	4973 lm
90 LED 45W/840 W 90 LED 45W/840 B	90°	45 W	80	4000 K	5850 lm
90 LED 45W/850 W 90 LED 45W/850 B	90°	45 W	80	5000 K	5850 lm
110 LED 20W/827 W 110 LED 20W/827 B	110°	20 W	80	2700 K	1846 lm
110 LED 20W/830 W 110 LED 20W/830 B	110°	20 W	80	3000 K	2210 lm
110 LED 20W/840 W 110 LED 20W/840 B	110°	20 W	80	4000 K	2600 lm
110 LED 20W/850 W 110 LED 20W/850 B	110°	20 W	80	5000 K	2600 lm
110 LED 32W/827 W 110 LED 32W/827 B	110°	32 W	80	2700 K	2954 lm
110 LED 32W/830 W 110 LED 32W/830 B	110°	32 W	80	3000 K	3536 lm
110 LED 32W/840 W 110 LED 32W/840 B	110°	32 W	80	4000 K	4160 lm
110 LED 32W/850 W 110 LED 32W/850 B	110°	32 W	80	5000 K	4160 lm
110 LED 45W/827 W 110 LED 45W/827 B	110°	45 W	80	2700 K	4154 lm
110 LED 45W/830 W 110 LED 45W/830 B	110°	45 W	80	3000 K	4973 lm
110 LED 45W/840 W 110 LED 45W/840 B	110°	45 W	80	4000 K	5850 lm
110 LED 45W/850 W 110 LED 45W/850 B	110°	45 W	80	5000 K	5850 lm
DS LED 20W/827 W DS LED 20W/827 B	Double Sym	20 W	80	2700 K	1846 lm
DS LED 20W/830 W DS LED 20W/830 B	Double Sym	20 W	80	3000 K	2210 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

Ordering information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
DS LED 20W/840 W DS LED 20W/840 B	Double Sym	20 W	80	4000 K	2600 lm
DS LED 20W/850 W DS LED 20W/850 B	Double Sym	20 W	80	5000 K	2600 lm
DS LED 32W/827 W DS LED 32W/827 B	Double Sym	32 W	80	2700 K	2954 lm
DS LED 32W/830 W DS LED 32W/830 B	Double Sym	32 W	80	3000 K	3536 lm
DS LED 32W/840 W DS LED 32W/840 B	Double Sym	32 W	80	4000 K	4160 lm
DS LED 32W/850 W DS LED 32W/850 B	Double Sym	32 W	80	5000 K	4160 lm
DS LED 45W/827 W DS LED 45W/827 B	Double Sym	45 W	80	2700 K	4154 lm
DS LED 45W/830 W DS LED 45W/830 B	Double Sym	45 W	80	3000 K	4973 lm
DS LED 45W/840 W DS LED 45W/840 B	Double Sym	45 W	80	4000 K	5850 lm
DS LED 45W/850 W DS LED 45W/850 B	Double Sym	45 W	80	5000 K	5850 lm
AS LED 20W/827 W AS LED 20W/827 B	ASym	20 W	80	2700 K	1846 lm
AS LED 20W/830 W AS LED 20W/830 B	ASym	20 W	80	3000 K	2210 lm
AS LED 20W/840 W AS LED 20W/840 B	ASym	20 W	80	4000 K	2600 lm
AS LED 20W/850 W AS LED 20W/850 B	ASym	20 W	80	5000 K	2600 lm
AS LED 32W/827 W AS LED 32W/827 B	ASym	32 W	80	2700 K	2954 lm
AS LED 32W/830 W AS LED 32W/830 B	ASym	32 W	80	3000 K	3536 lm
AS LED 32W/840 W AS LED 32W/840 B	ASym	32 W	80	4000 K	4160 lm
AS LED 32W/850 W AS LED 32W/850 B	ASym	32 W	80	5000 K	4160 lm
AS LED 45W/827 W AS LED 45W/827 B	ASym	45 W	80	2700 K	4154 lm
AS LED 45W/830 W AS LED 45W/830 B	ASym	45 W	80	3000 K	4973 lm
AS LED 45W/840 W AS LED 45W/840 B	ASym	45 W	80	4000 K	5850 lm
AS LED 45W/850 W AS LED 45W/850 B	ASym	45 W	80	5000 K	5850 lm
30 LED 20W/927 W 30 LED 20W/927 B	30°	20 W	90	2700 K	1612 lm
30 LED 20W/930 W 30 LED 20W/930 B	30°	20 W	90	3000 K	1950 lm
30 LED 20W/940 W 30 LED 20W/940 B	30°	20 W	90	4000 K	2275 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

Ordering information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
30 LED 20W/950 W 30 LED 20W/950 B	30°	20 W	90	5000 K	2275 lm
30 LED 32W/927 W 30 LED 32W/927 B	30°	32 W	90	2700 K	2579 lm
30 LED 32W/930 W 30 LED 32W/930 B	30°	32 W	90	3000 K	3120 lm
30 LED 32W/940 W 30 LED 32W/940 B	30°	32 W	90	4000 K	3640 lm
30 LED 32W/950 W 30 LED 32W/950 B	30°	32 W	90	5000 K	3640 lm
30 LED 45W/927 W 30 LED 45W/927 B	30°	45 W	90	2700 K	3627 lm
30 LED 45W/930 W 30 LED 45W/930 B	30°	45 W	90	3000 K	4388 lm
30 LED 45W/940 W 30 LED 45W/940 B	30°	45 W	90	4000 K	5119 lm
30 LED 45W/950 W 30 LED 45W/950 B	30°	45 W	90	5000 K	5119 lm
60 LED 20W/927 W 60 LED 20W/927 B	60°	20 W	90	2700 K	1612 lm
60 LED 20W/930 W 60 LED 20W/930 B	60°	20 W	90	3000 K	1950 lm
60 LED 20W/940 W 60 LED 20W/940 B	60°	20 W	90	4000 K	2275 lm
60 LED 20W/950 W 60 LED 20W/950 B	60°	20 W	90	5000 K	2275 lm
60 LED 32W/927 W 60 LED 32W/927 B	60°	32 W	90	2700 K	2579 lm
60 LED 32W/930 W 60 LED 32W/930 B	60°	32 W	90	3000 K	3120 lm
60 LED 32W/940 W 60 LED 32W/940 B	60°	32 W	90	4000 K	3640 lm
60 LED 32W/950 W 60 LED 32W/950 B	60°	32 W	90	5000 K	3640 lm
60 LED 45W/927 W 60 LED 45W/927 B	60°	45 W	90	2700 K	3627 lm
60 LED 45W/930 W 60 LED 45W/930 B	60°	45 W	90	3000 K	4388 lm
60 LED 45W/940 W 60 LED 45W/940 B	60°	45 W	90	4000 K	5119 lm
60 LED 45W/950 W 60 LED 45W/950 B	60°	45 W	90	5000 K	5119 lm
90 LED 20W/927 W 90 LED 20W/927 B	90°	20 W	90	2700 K	1612 lm
90 LED 20W/930 W 90 LED 20W/930 B	90°	20 W	90	3000 K	1950 lm
90 LED 20W/940 W 90 LED 20W/940 B	90°	20 W	90	4000 K	2275 lm
90 LED 20W/950 W 90 LED 20W/950 B	90°	20 W	90	5000 K	2275 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra> 80 /> 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

Ordering information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
90 LED 32W/927 W 90 LED 32W/927 B	90°	32 W	90	2700 K	2579 lm
90 LED 32W/930 W 90 LED 32W/930 B	90°	32 W	90	3000 K	3120 lm
90 LED 32W/940 W 90 LED 32W/940 B	90°	32 W	90	4000 K	3640 lm
90 LED 32W/950 W 90 LED 32W/950 B	90°	32 W	90	5000 K	3640 lm
90 LED 45W/927 W 90 LED 45W/927 B	90°	45 W	90	2700 K	3627 lm
90 LED 45W/930 W 90 LED 45W/930 B	90°	45 W	90	3000 K	4388 lm
90 LED 45W/940 W 90 LED 45W/940 B	90°	45 W	90	4000 K	5119 lm
90 LED 45W/950 W 90 LED 45W/950 B	90°	45 W	90	5000 K	5119 lm
110 LED 20W/927 W 110 LED 20W/927 B	110°	20 W	90	2700 K	1612 lm
110 LED 20W/930 W 110 LED 20W/930 B	110°	20 W	90	3000 K	1950 lm
110 LED 20W/940 W 110 LED 20W/940 B	110°	20 W	90	4000 K	2275 lm
110 LED 20W/950 W 110 LED 20W/950 B	110°	20 W	90	5000 K	2275 lm
110 LED 32W/927 W 110 LED 32W/927 B	110°	32 W	90	2700 K	2579 lm
110 LED 32W/930 W 110 LED 32W/930 B	110°	32 W	90	3000 K	3120 lm
110 LED 32W/940 W 110 LED 32W/940 B	110°	32 W	90	4000 K	3640 lm
110 LED 32W/950 W 110 LED 32W/950 B	110°	32 W	90	5000 K	3640 lm
110 LED 45W/927 W 110 LED 45W/927 B	110°	45 W	90	2700 K	3627 lm
110 LED 45W/930 W 110 LED 45W/930 B	110°	45 W	90	3000 K	4388 lm
110 LED 45W/940 W 110 LED 45W/940 B	110°	45 W	90	4000 K	5119 lm
110 LED 45W/950 W 110 LED 45W/950 B	110°	45 W	90	5000 K	5119 lm
DS LED 20W/927 W DS LED 20W/927 B	Double Sym	20 W	90	2700 K	1612 lm
DS LED 20W/930 W DS LED 20W/930 B	Double Sym	20 W	90	3000 K	1950 lm
DS LED 20W/940 W DS LED 20W/940 B	Double Sym	20 W	90	4000 K	2275 lm
DS LED 20W/950 W DS LED 20W/950 B	Double Sym	20 W	90	5000 K	2275 lm
DS LED 32W/927 W DS LED 32W/927 B	Double Sym	32 W	90	2700 K	2579 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

Ordering information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
DS LED 32W/930 W DS LED 32W/930 B	Double Sym	32 W	90	3000 K	3120 lm
DS LED 32W/940 W DS LED 32W/940 B	Double Sym	32 W	90	4000 K	3640 lm
DS LED 32W/950 W DS LED 32W/950 B	Double Sym	32 W	90	5000 K	3640 lm
DS LED 45W/927 W DS LED 45W/927 B	Double Sym	45 W	90	2700 K	3627 lm
DS LED 45W/930 W DS LED 45W/930 B	Double Sym	45 W	90	3000 K	4388 lm
DS LED 45W/940 W DS LED 45W/940 B	Double Sym	45 W	90	4000 K	5119 lm
DS LED 45W/950 W DS LED 45W/950 B	Double Sym	45 W	90	5000 K	5119 lm
AS LED 20W/927 W AS LED 20W/927 B	ASym	20 W	90	2700 K	1612 lm
AS LED 20W/930 W AS LED 20W/930 B	ASym	20 W	90	3000 K	1950 lm
AS LED 20W/940 W AS LED 20W/940 B	ASym	20 W	90	4000 K	2275 lm
AS LED 20W/950 W AS LED 20W/950 B	ASym	20 W	90	5000 K	2275 lm
AS LED 32W/927 W AS LED 32W/927 B	ASym	32 W	90	2700 K	2579 lm
AS LED 32W/930 W AS LED 32W/930 B	ASym	32 W	90	3000 K	3120 lm
AS LED 32W/940 W AS LED 32W/940 B	ASym	32 W	90	4000 K	3640 lm
AS LED 32W/950 W AS LED 32W/950 B	ASym	32 W	90	5000 K	3640 lm
AS LED 45W/927 W AS LED 45W/927 B	ASym	45 W	90	2700 K	3627 lm
AS LED 45W/930 W AS LED 45W/930 B	ASym	45 W	90	3000 K	4388 lm
AS LED 45W/940 W AS LED 45W/940 B	ASym	45 W	90	4000 K	5119 lm
AS LED 45W/950 W AS LED 45W/950 B	ASym	45 W	90	5000 K	5119 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.