



Type of luminaire	linear light
Application areas	general lighting
Mounting	Surface-mounted / recessed / pendant
Supply unit	LED Driver integrated (LED Driver DALI on request)
Nominal voltage	220V, 50Hz
System performance	25 W, 30 W, 40 W, 50 W, 60 W, 80 W
Lighting technology	LED SMD 2835
Optic	PC
Beam angle	60°, 90°, DoubleSym, Asym
Luminous Flux	3712 - 11880 lm
Light colour	2700 K, 3000 K, 4000 K, 5000 K
CRI	80 - 90
Power factor	0,95
Protection rating	IP20
Cooling	passive
Body	aluminum
Body colour	black, white, Special colours on request
Dimensions	1694x46x47 mm
Weight	2,5 kg
Life time	50 000 hours.
Warranty	5 years/50 000 hours
Certificates	UA, CE




**Beam angle options**




**Baseline 1700 60 LED**



**Baseline 1700 90 LED**



**Baseline 1700 DS LED**



**Baseline 1700 AS LED**

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

## Ordering Information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
60 LED 25W/827 W 60 LED 25W/827 B	60°	25 W	80	2700 K	2636 lm
60 LED 25W/830 W 60 LED 25W/830 B	60°	25 W	80	3000 K	3156 lm
60 LED 25W/840 W 60 LED 25W/840 B	60°	25 W	80	4000 K	3713 lm
60 LED 25W/850 W 60 LED 25W/850 B	60°	25 W	80	5000 K	3713 lm
90 LED 25W/827 W 90 LED 25W/827 B	90°	25 W	80	2700 K	2636 lm
90 LED 25W/830 W 90 LED 25W/830 B	90°	25 W	80	3000 K	3156 lm
90 LED 25W/840 W 90 LED 25W/840 B	90°	25 W	80	4000 K	3713 lm
90 LED 25W/850 W 90 LED 25W/850 B	90°	25 W	80	5000 K	3713 lm
DS LED 25W/827 W DS LED 25W/827 B	DS	25 W	80	2700 K	2636 lm
DS LED 25W/830 W DS LED 25W/830 B	DS	25 W	80	3000 K	3156 lm
DS LED 25W/840 W DS LED 25W/840 B	DS	25 W	80	4000 K	3713 lm
DS LED 25W/850 W DS LED 25W/850 B	DS	25 W	80	5000 K	3713 lm
AS LED 25W/827 W AS LED 25W/827 B	AS	25 W	80	2700 K	2636 lm
AS LED 25W/830 W AS LED 25W/830 B	AS	25 W	80	3000 K	3156 lm
AS LED 25W/840 W AS LED 25W/840 B	AS	25 W	80	4000 K	3713 lm
AS LED 25W/850 W AS LED 25W/850 B	AS	25 W	80	5000 K	3713 lm
60 LED 30W/827 W 60 LED 30W/827 B	60°	30 W	80	2700 K	3163 lm
60 LED 30W/830 W 60 LED 30W/830 B	60°	30 W	80	3000 K	3787 lm
60 LED 30W/840 W 60 LED 30W/840 B	60°	30 W	80	4000 K	4455 lm
60 LED 30W/850 W 60 LED 30W/850 B	60°	30 W	80	5000 K	4455 lm
90 LED 30W/827 W 90 LED 30W/827 B	90°	30 W	80	2700 K	3163 lm
90 LED 30W/830 W 90 LED 30W/830 B	90°	30 W	80	3000 K	3787 lm
90 LED 30W/840 W 90 LED 30W/840 B	90°	30 W	80	4000 K	4455 lm
90 LED 30W/850 W 90 LED 30W/850 B	90°	30 W	80	5000 K	4455 lm
DS LED 30W/827 W DS LED 30W/827 B	DS	30 W	80	2700 K	3163 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

## Ordering Information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
DS LED 30W/830 W DS LED 30W/830 B	DS	30 W	80	3000 K	3787 lm
DS LED 30W/840 W DS LED 30W/840 B	DS	30 W	80	4000 K	4455 lm
DS LED 30W/850 W DS LED 30W/850 B	DS	30 W	80	5000 K	4455 lm
AS LED 30W/827 W AS LED 30W/827 B	AS	30 W	80	2700 K	3163 lm
AS LED 30W/830 W AS LED 30W/830 B	AS	30 W	80	3000 K	3787 lm
AS LED 30W/840 W AS LED 30W/840 B	AS	30 W	80	4000 K	4455 lm
AS LED 30W/850 W AS LED 30W/850 B	AS	30 W	80	5000 K	4455 lm
60 LED 40W/827 W 60 LED 40W/827 B	60°	40 W	80	2700 K	4217 lm
60 LED 40W/830 W 60 LED 40W/830 B	60°	40 W	80	3000 K	5049 lm
60 LED 40W/840 W 60 LED 40W/840 B	60°	40 W	80	4000 K	5940 lm
60 LED 40W/850 W 60 LED 40W/850 B	60°	40 W	80	5000 K	5940 lm
90 LED 40W/827 W 90 LED 40W/827 B	90°	40 W	80	2700 K	4217 lm
90 LED 40W/830 W 90 LED 40W/830 B	90°	40 W	80	3000 K	5049 lm
90 LED 40W/840 W 90 LED 40W/840 B	90°	40 W	80	4000 K	5940 lm
90 LED 40W/850 W 90 LED 40W/850 B	90°	40 W	80	5000 K	5940 lm
DS LED 40W/827 W DS LED 40W/827 B	DS	40 W	80	2700 K	4217 lm
DS LED 40W/830 W DS LED 40W/830 B	DS	40 W	80	3000 K	5049 lm
DS LED 40W/840 W DS LED 40W/840 B	DS	40 W	80	4000 K	5940 lm
DS LED 40W/850 W DS LED 40W/850 B	DS	40 W	80	5000 K	5940 lm
AS LED 40W/827 W AS LED 40W/827 B	AS	40 W	80	2700 K	4217 lm
AS LED 40W/830 W AS LED 40W/830 B	AS	40 W	80	3000 K	5049 lm
AS LED 40W/840 W AS LED 40W/840 B	AS	40 W	80	4000 K	5940 lm
AS LED 40W/850 W AS LED 40W/850 B	AS	40 W	80	5000 K	5940 lm
60 LED 50W/827 W 60 LED 50W/827 B	60°	50 W	80	2700 K	5272 lm
60 LED 50W/830 W 60 LED 50W/830 B	60°	50 W	80	3000 K	6311 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

## Ordering Information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
60 LED 50W/840 W 60 LED 50W/840 B	60°	50 W	80	4000 K	7425 lm
60 LED 50W/850 W 60 LED 50W/850 B	60°	50 W	80	5000 K	7425 lm
90 LED 50W/827 W 90 LED 50W/827 B	90°	50 W	80	2700 K	5272 lm
90 LED 50W/830 W 90 LED 50W/830 B	90°	50 W	80	3000 K	6311 lm
90 LED 50W/840 W 90 LED 50W/840 B	90°	50 W	80	4000 K	7425 lm
90 LED 50W/850 W 90 LED 50W/850 B	90°	50 W	80	5000 K	7425 lm
DS LED 50W/827 W DS LED 50W/827 B	DS	50 W	80	2700 K	5272 lm
DS LED 50W/830 W DS LED 50W/830 B	DS	50 W	80	3000 K	6311 lm
DS LED 50W/840 W DS LED 50W/840 B	DS	50 W	80	4000 K	7425 lm
DS LED 50W/850 W DS LED 50W/850 B	DS	50 W	80	5000 K	7425 lm
AS LED 50W/827 W AS LED 50W/827 B	AS	50 W	80	2700 K	5272 lm
AS LED 50W/830 W AS LED 50W/830 B	AS	50 W	80	3000 K	6311 lm
AS LED 50W/840 W AS LED 50W/840 B	AS	50 W	80	4000 K	7425 lm
AS LED 50W/850 W AS LED 50W/850 B	AS	50 W	80	5000 K	7425 lm
60 LED 60W/827 W 60 LED 60W/827 B	60°	60 W	80	2700 K	6326 lm
60 LED 60W/830 W 60 LED 60W/830 B	60°	60 W	80	3000 K	7574 lm
60 LED 60W/840 W 60 LED 60W/840 B	60°	60 W	80	4000 K	8910 lm
60 LED 60W/850 W 60 LED 60W/850 B	60°	60 W	80	5000 K	8910 lm
90 LED 60W/827 W 90 LED 60W/827 B	90°	60 W	80	2700 K	6326 lm
90 LED 60W/830 W 90 LED 60W/830 B	90°	60 W	80	3000 K	7574 lm
90 LED 60W/840 W 90 LED 60W/840 B	90°	60 W	80	4000 K	8910 lm
90 LED 60W/850 W 90 LED 60W/850 B	90°	60 W	80	5000 K	8910 lm
DS LED 60W/827 W DS LED 60W/827 B	DS	60 W	80	2700 K	6326 lm
DS LED 60W/830 W DS LED 60W/830 B	DS	60 W	80	3000 K	7574 lm
DS LED 60W/840 W DS LED 60W/840 B	DS	60 W	80	4000 K	8910 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

## Ordering Information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
DS LED 60W/850 W DS LED 60W/850 B	DS	60 W	80	5000 K	8910 lm
AS LED 60W/827 W AS LED 60W/827 B	AS	60 W	80	2700 K	6326 lm
AS LED 60W/830 W AS LED 60W/830 B	AS	60 W	80	3000 K	7574 lm
AS LED 60W/840 W AS LED 60W/840 B	AS	60 W	80	4000 K	8910 lm
AS LED 60W/850 W AS LED 60W/850 B	AS	60 W	80	5000 K	8910 lm
60 LED 80W/827 W 60 LED 80W/827 B	60°	80 W	80	2700 K	8435 lm
60 LED 80W/830 W 60 LED 80W/830 B	60°	80 W	80	3000 K	10098 lm
60 LED 80W/840 W 60 LED 80W/840 B	60°	80 W	80	4000 K	11880 lm
60 LED 80W/850 W 60 LED 80W/850 B	60°	80 W	80	5000 K	11880 lm
90 LED 80W/827 W 90 LED 80W/827 B	90°	80 W	80	2700 K	8435 lm
90 LED 80W/830 W 90 LED 80W/830 B	90°	80 W	80	3000 K	10098 lm
90 LED 80W/840 W 90 LED 80W/840 B	90°	80 W	80	4000 K	11880 lm
90 LED 80W/850 W 90 LED 80W/850 B	90°	80 W	80	5000 K	11880 lm
DS LED 80W/827 W DS LED 80W/827 B	DS	80 W	80	2700 K	8435 lm
DS LED 80W/830 W DS LED 80W/830 B	DS	80 W	80	3000 K	10098 lm
DS LED 80W/840 W DS LED 80W/840 B	DS	80 W	80	4000 K	11880 lm
DS LED 80W/850 W DS LED 80W/850 B	DS	80 W	80	5000 K	11880 lm
AS LED 80W/827 W AS LED 80W/827 B	AS	80 W	80	2700 K	8435 lm
AS LED 80W/830 W AS LED 80W/830 B	AS	80 W	80	3000 K	10098 lm
AS LED 80W/840 W AS LED 80W/840 B	AS	80 W	80	4000 K	11880 lm
AS LED 80W/850 W AS LED 80W/850 B	AS	80 W	80	5000 K	11880 lm
60 LED 25W/927 W 60 LED 25W/927 B	60°	25 W	90	2700 K	2302 lm
60 LED 25W/930 W 60 LED 25W/930 B	60°	25 W	90	3000 K	2784 lm
60 LED 25W/940 W 60 LED 25W/940 B	60°	25 W	90	4000 K	3248 lm
60 LED 25W/950 W 60 LED 25W/950 B	60°	25 W	90	5000 K	3248 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

## Ordering Information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
90 LED 25W/927 W 90 LED 25W/927 B	90°	25 W	90	2700 K	2302 lm
90 LED 25W/930 W 90 LED 25W/930 B	90°	25 W	90	3000 K	2784 lm
90 LED 25W/940 W 90 LED 25W/940 B	90°	25 W	90	4000 K	3248 lm
90 LED 25W/950 W 90 LED 25W/950 B	90°	25 W	90	5000 K	3248 lm
DS LED 25W/927 W DS LED 25W/927 B	DS	25 W	90	2700 K	2302 lm
DS LED 25W/930 W DS LED 25W/930 B	DS	25 W	90	3000 K	2784 lm
DS LED 25W/940 W DS LED 25W/940 B	DS	25 W	90	4000 K	3248 lm
DS LED 25W/950 W DS LED 25W/950 B	DS	25 W	90	5000 K	3248 lm
AS LED 25W/927 W AS LED 25W/927 B	AS	25 W	90	2700 K	2302 lm
AS LED 25W/930 W AS LED 25W/930 B	AS	25 W	90	3000 K	2784 lm
AS LED 25W/940 W AS LED 25W/940 B	AS	25 W	90	4000 K	3248 lm
AS LED 25W/950 W AS LED 25W/950 B	AS	25 W	90	5000 K	3248 lm
60 LED 30W/927 W 60 LED 30W/927 B	60°	30 W	90	2700 K	2762 lm
60 LED 30W/930 W 60 LED 30W/930 B	60°	30 W	90	3000 K	3341 lm
60 LED 30W/940 W 60 LED 30W/940 B	60°	30 W	90	4000 K	3898 lm
60 LED 30W/950 W 60 LED 30W/950 B	60°	30 W	90	5000 K	3898 lm
90 LED 30W/927 W 90 LED 30W/927 B	90°	30 W	90	2700 K	2762 lm
90 LED 30W/930 W 90 LED 30W/930 B	90°	30 W	90	3000 K	3341 lm
90 LED 30W/940 W 90 LED 30W/940 B	90°	30 W	90	4000 K	3898 lm
90 LED 30W/950 W 90 LED 30W/950 B	90°	30 W	90	5000 K	3898 lm
DS LED 30W/927 W DS LED 30W/927 B	DS	30 W	90	2700 K	2762 lm
DS LED 30W/930 W DS LED 30W/930 B	DS	30 W	90	3000 K	3341 lm
DS LED 30W/940 W DS LED 30W/940 B	DS	30 W	90	4000 K	3898 lm
DS LED 30W/950 W DS LED 30W/950 B	DS	30 W	90	5000 K	3898 lm
AS LED 30W/927 W AS LED 30W/927 B	AS	30 W	90	2700 K	2762 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.

## Ordering Information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
AS LED 30W/930 W AS LED 30W/930 B	AS	30 W	90	3000 K	3341 lm
AS LED 30W/940 W AS LED 30W/940 B	AS	30 W	90	4000 K	3898 lm
AS LED 30W/950 W AS LED 30W/950 B	AS	30 W	90	5000 K	3898 lm
60 LED 40W/927 W 60 LED 40W/927 B	60°	40 W	90	2700 K	3683 lm
60 LED 40W/930 W 60 LED 40W/930 B	60°	40 W	90	3000 K	4455 lm
60 LED 40W/940 W 60 LED 40W/940 B	60°	40 W	90	4000 K	5198 lm
60 LED 40W/950 W 60 LED 40W/950 B	60°	40 W	90	5000 K	5198 lm
90 LED 40W/927 W 90 LED 40W/927 B	90°	40 W	90	2700 K	3683 lm
90 LED 40W/930 W 90 LED 40W/930 B	90°	40 W	90	3000 K	4455 lm
90 LED 40W/940 W 90 LED 40W/940 B	90°	40 W	90	4000 K	5198 lm
90 LED 40W/950 W 90 LED 40W/950 B	90°	40 W	90	5000 K	5198 lm
DS LED 40W/927 W DS LED 40W/927 B	DS	40 W	90	2700 K	3683 lm
DS LED 40W/930 W DS LED 40W/930 B	DS	40 W	90	3000 K	4455 lm
DS LED 40W/940 W DS LED 40W/940 B	DS	40 W	90	4000 K	5198 lm
DS LED 40W/950 W DS LED 40W/950 B	DS	40 W	90	5000 K	5198 lm
AS LED 40W/927 W AS LED 40W/927 B	AS	40 W	90	2700 K	3683 lm
AS LED 40W/930 W AS LED 40W/930 B	AS	40 W	90	3000 K	4455 lm
AS LED 40W/940 W AS LED 40W/940 B	AS	40 W	90	4000 K	5198 lm
AS LED 40W/950 W AS LED 40W/950 B	AS	40 W	90	5000 K	5198 lm
60 LED 50W/927 W 60 LED 50W/927 B	60°	50 W	90	2700 K	4604 lm
60 LED 50W/930 W 60 LED 50W/930 B	60°	50 W	90	3000 K	5569 lm
60 LED 50W/940 W 60 LED 50W/940 B	60°	50 W	90	4000 K	6497 lm
60 LED 50W/950 W 60 LED 50W/950 B	60°	50 W	90	5000 K	6497 lm
90 LED 50W/927 W 90 LED 50W/927 B	90°	50 W	90	2700 K	4604 lm
90 LED 50W/930 W 90 LED 50W/930 B	90°	50 W	90	3000 K	5569 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.



## Ordering Information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
90 LED 50W/940 W 90 LED 50W/940 B	90°	50 W	90	4000 K	6497 lm
90 LED 50W/950 W 90 LED 50W/950 B	90°	50 W	90	5000 K	6497 lm
DS LED 50W/927 W DS LED 50W/927 B	DS	50 W	90	2700 K	4604 lm
DS LED 50W/930 W DS LED 50W/930 B	DS	50 W	90	3000 K	5569 lm
DS LED 50W/940 W DS LED 50W/940 B	DS	50 W	90	4000 K	6497 lm
DS LED 50W/950 W DS LED 50W/950 B	DS	50 W	90	5000 K	6497 lm
AS LED 50W/927 W AS LED 50W/927 B	AS	50 W	90	2700 K	4604 lm
AS LED 50W/930 W AS LED 50W/930 B	AS	50 W	90	3000 K	5569 lm
AS LED 50W/940 W AS LED 50W/940 B	AS	50 W	90	4000 K	6497 lm
AS LED 50W/950 W AS LED 50W/950 B	AS	50 W	90	5000 K	6497 lm
60 LED 60W/927 W 60 LED 60W/927 B	60°	60 W	90	2700 K	5524 lm
60 LED 60W/930 W 60 LED 60W/930 B	60°	60 W	90	3000 K	6683 lm
60 LED 60W/940 W 60 LED 60W/940 B	60°	60 W	90	4000 K	7796 lm
60 LED 60W/950 W 60 LED 60W/950 B	60°	60 W	90	5000 K	7796 lm
90 LED 60W/927 W 90 LED 60W/927 B	90°	60 W	90	2700 K	5524 lm
90 LED 60W/930 W 90 LED 60W/930 B	90°	60 W	90	3000 K	6683 lm
90 LED 60W/940 W 90 LED 60W/940 B	90°	60 W	90	4000 K	7796 lm
90 LED 60W/950 W 90 LED 60W/950 B	90°	60 W	90	5000 K	7796 lm
DS LED 60W/927 W DS LED 60W/927 B	DS	60 W	90	2700 K	5524 lm
DS LED 60W/930 W DS LED 60W/930 B	DS	60 W	90	3000 K	6683 lm
DS LED 60W/940 W DS LED 60W/940 B	DS	60 W	90	4000 K	7796 lm
DS LED 60W/950 W DS LED 60W/950 B	DS	60 W	90	5000 K	7796 lm
AS LED 60W/927 W AS LED 60W/927 B	AS	60 W	90	2700 K	5524 lm
AS LED 60W/930 W AS LED 60W/930 B	AS	60 W	90	3000 K	6683 lm
AS LED 60W/940 W AS LED 60W/940 B	AS	60 W	90	4000 K	7796 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.



## Ordering Information

Model	Beam angle	System performance	CRI	Light colour White	Luminous Flux
AS LED 60W/950 W AS LED 60W/950 B	AS	60 W	90	5000 K	7796 lm
60 LED 80W/927 W 60 LED 80W/927 B	60°	80 W	90	2700 K	7366 lm
60 LED 80W/930 W 60 LED 80W/930 B	60°	80 W	90	3000 K	8910 lm
60 LED 80W/940 W 60 LED 80W/940 B	60°	80 W	90	4000 K	10395 lm
60 LED 80W/950 W 60 LED 80W/950 B	60°	80 W	90	5000 K	10395 lm
90 LED 80W/927 W 90 LED 80W/927 B	90°	80 W	90	2700 K	7366 lm
90 LED 80W/930 W 90 LED 80W/930 B	90°	80 W	90	3000 K	8910 lm
90 LED 80W/940 W 90 LED 80W/940 B	90°	80 W	90	4000 K	10395 lm
90 LED 80W/950 W 90 LED 80W/950 B	90°	80 W	90	5000 K	10395 lm
DS LED 80W/927 W DS LED 80W/927 B	DS	80 W	90	2700 K	7366 lm
DS LED 80W/930 W DS LED 80W/930 B	DS	80 W	90	3000 K	8910 lm
DS LED 80W/940 W DS LED 80W/940 B	DS	80 W	90	4000 K	10395 lm
DS LED 80W/950 W DS LED 80W/950 B	DS	80 W	90	5000 K	10395 lm
AS LED 80W/927 W AS LED 80W/927 B	AS	80 W	90	2700 K	7366 lm
AS LED 80W/930 W AS LED 80W/930 B	AS	80 W	90	3000 K	8910 lm
AS LED 80W/940 W AS LED 80W/940 B	AS	80 W	90	4000 K	10395 lm
AS LED 80W/950 W AS LED 80W/950 B	AS	80 W	90	5000 K	10395 lm

Technical details, as well as size and weight parameters were prepared as accurately as possible. All dimensions in mm. LED Lifetime Information - L90 / B10 at 25 ° C ambient temperature. A tolerance of +/- 10% applies to luminous flux and performance characteristics. Minimum color rendering indices Ra > 80 / > 90. Product images are used as an example and may differ from the original. We reserve the right to make changes in order to improve the product.